



ATTIVA FLEET.6



48 VOLT WITH DC SYSTEM

6 X 8V LEAD-ACID BATTERIES

205/50-10 ALUMINUM RIMS

FRONT & REAR LED LIGHTS

MECHANICAL BRAKES ON REAR
WHEELS

R.03 - FEB.23

ATTIVA FLEET.6



ITALCAR is an Italian brand

places:	2
batteries:	6 x 8V, US8VCG standard
motor:	DC 3kW 48V – ADC
controller:	Curtis 1266A– DC – 275A
transmission:	rear axle, 19 spline, ratio 12,31:1
steering:	self compensating single reduction rack and pignon
performances:	
suggested max speed	22 km/h
range	36 holes
max hill climbing ability	25% (then 14°)
vehicle dimensions:	
overall	2400mm x 1200mm x 1800mm
ground clearance (empty):	210mm
turning radius (min):	2,9 mt
wheel base	1650mm
chassis:	galvanized steel frame and powder coated
body:	PP impregnated and painted
suspensions:	
front	Independent suspensions
rear	leaf springs with hydraulic shock absorbers
brakes:	mechanical brakes on rear wheel
rear	drum
tyres:	205 / 50 – 10 with aluminium rims
recommended pressure (max):	2,1 bar (30psi)
battery charger:	included with the vehicle - 48v, 220/230V
basic configuration:	Includes: brown seats, reverse buzzer, front and rear LED lights, horn, direction indicators, rear-view mirrors, one piece plexiglass

seguici su - follow us on



clicca mi piace - like us on



all above specification were correct at the time of the publishing and are indicatives and not binding.
ITALCAR INDUSTRIAL Srl maintains the right to bring any changes without notice