

ITALCAR INDUSTRIAL S.r.I. – Via Bruino, 36 – 10040 Rivalta di Torino tel. 011.9040225 – fax 011.9032986



www.italcar.com - info@italcar.com







MODEL ATTIVA AMBULANCE.4 48 V

TECHNICAL FEATURES – ATTIVA AMBULANCE.4 48V

ENGINE: DC 48V - ADC **VOLTAGE:** 48 volt front: independent suspension SUSPENSION: **BATTERIES:** 6 x 8volt mod. US battery 8VGC rear: leaf springs with hydraulic shock absorbers **CHASSIS** galvanized steel frame and powder coated CONTROLLER: electronic engine SEM BODY: main body: PP impregnated and painted Curtis, mod. 1266 with feature walk away equipped for the transport of injured people PERFORMANCES: 30 km/h * max speed: * range: 80 km. TRANSMISSION: rear axle, 19 spline, ratio 12,31:1 * hill climbing ability: 15% datas are to be considered indicative and calculated on the average of different conditions of use STEERING: self compensating single reduction rack and pignon TYRES: 205 / 50 - 10 - aluminium rims self-adjusting dual rear wheel mechanical drum brakes **BRAKES:** BATTERY CHARGER: included with the vehicle. 48v, 220/230V **OVERALL DIMENSIONS:** length 2800mm **BASIC CONFIGURATION:** width 1180mm reverse buzzer, digital speedometer, foldable alloy stretcher with security belts, front height (max) 2150mm and rear lights, horn, direction indicators, rear-view mirrors, plexiglass **COLOURS:** white **TURNING RADIUS:** 3 mt

All data reported are indicatives and not binding. ITALCAR INDUSTRIAL S.r.l. maintains the right to bring any changes without notice