



ATTIVA XTR 2.6



48 VOLT WITH AC SYSTEM

6 X 8V LEAD-ACID BATTERIES

22X11-12 ALUMINUM RIMS

FRONT & REAR LED LIGHTS

HYDRAULIC BRAKES ON 4
WHEELS + HANDBRAKE

ITALCAR INDUSTRIAL SRL | Via Bruino, 36 | 10040 Rivalta di Torino (TO)
Tel. +39 011 9040225 | Fax +39 011 9032986 | info@italcar.com | www.italcar.com



ATTIVA XTR 2.6

places:	2
batteries:	6 x 8V, US8VGC standard
motor:	AC 48V – Mahle Letrika
controller:	sevcon GEN4 – AC – 450A
transmission:	rear axle, 19 spline, ratio 16:1
steering:	self compensating single reduction rack and pignon
performances:	
suggested max speed	30 km/h
range	80 km
max hill climbing ability	20% (then 11°)
vehicle dimensions:	
overall	3000mm x 1400mm x 2150mm
cargo dimensions:	
overall	900mm x 1100mm x 240mm
ground clearance (empty):	350 mm
turning radius (min):	3,5 mt
wheel base	1710 mm
chassis:	galvanized steel frame and powder coated
body:	PP impregnated and painted
suspensions:	
front	independent suspensions
rear	leaf springs with hydraulic shock absorbers
brakes:	automotive types, double hydraulic circuit on four wheel
front	disc
rear	disc
tyres:	22x11-12 with aluminum rims
recommended pressure:	2 bar (29psi)
battery charger:	included with the vehicle - 48v, 220/230V
basic configuration:	Includes: reverse buzzer; digital speedometer, front and rear LED lights, horn, direction indicators, rear-view mirrors, one piece plexiglass

*all above specification were correct at the time of the publishing and are indicatives and not binding.
ITALCAR INDUSTRIAL Srl maintains the right to bring any changes without notice*



ITALCAR is an Italian brand

seguici su - follow us on



clicca mi piace - like us on

