



ATTIVA 2.6



48 VOLT WITH AC SYSTEM

6 X 8V LEAD-ACID BATTERIES

205/50-10 ALUMINUM RIMS

FRONT & REAR LED LIGHTS

HYDRAULIC BRAKES ON 4
WHEELS + HANDBRAKE

R.03 - FEB.23



ATTIVA 2.6

places:	2
batteries:	6 x 8V, US8VGC standard
motor:	AC 48V – Mahle Letrika
controller:	sevcon GEN4 – AC – 450A
transmission:	rear axle, 19 spline, ratio 16:1
steering:	self compensating single reduction rack and pignon
performances:	
suggested max speed	30 km/h
range	80 km
max hill climbing ability	25% (then 14°)
vehicle dimensions:	
overall	2800mm x 1200mm x 1800mm
cargo dimensions:	
overall	900mm x 1100mm x 240mm
ground clearance (empty):	210 mm
turning radius (min):	2,9 mt
wheel base	1650 mm
chassis:	galvanized steel frame and powder coated
body:	PP impregnated and painted
suspensions:	
front	Independent suspensions
rear	leaf springs with hydraulic shock absorbers
brakes:	automotive types, double hydraulic circuit on four wheel
front	disc
rear	drum
tyres:	205 / 50 – 10 with aluminium rims
recommended pressure:	1,7 bar (25psi)
battery charger:	included with the vehicle - 48v, 220/230V
basic configuration:	reverse buzzer; dash touch display, front and rear LED lights, horn, direction indicators, rear-view mirrors, one piece plexiglass

*all above specification were correct at the time of the publishing and are indicatives and not binding.
ITALCAR INDUSTRIAL Srl maintains the right to bring any changes without notice*



ITALCAR is an Italian brand

seguici su - follow us on



clicca mi piace - like us on

