



ITALCAR INDUSTRIAL S.r.l. – Via Bruino, 36 – 10040 Rivalta di Torino
tel. 011.9040225 – fax 011.9032986
www.italcar.com - info@italcar.com



MODELLO ATTIVA 2.4RS 48V

Veicolo 2 Posti – servizio “Room Service”

DATI TECNICI – ATTIVA 2.4RS 48V

MOTORE:	AC 48v -- iskra	VOLTAGGIO:	48 volt
BATTERIE:	8 x 6v - mod. US battery 2200	SOSPENSIONI:	ant: sospensioni indipendenti post: balestre con ammortizzatori idraulici
CONTROLLO:	SEVCON mod. GEN4 – 450Ah	TELAIO:	in acciaio galvanizzato con verniciatura a polvere.
		CARROZZERIA:	PP impregnato e verniciato 2 Posti + vanbox isothermico
TRASMISSIONE:	trazione posteriore, a 19 denti, ratio 12,31:1	PRESTAZIONI:	*velocità massima: 30 km/h * autonomia: 80 km * pendenza: 15%
			I dati sono da considerarsi indicativi e sono stati calcolati dalla media delle differenti condizioni di utilizzo
STERZO:	a cremagliera di tipo automobilistico	PNEUMATICI:	205/ 50 – 10 - cerchi in lega
FRENI:	ad azionamento idraulico sulle 4 ruote con circuito sdoppiato * Anteriori: a disco * Posteriori: a tamburo freno di stazionamento a mano	CARICA BATTERIE:	In dotazione al veicolo 48v, 220/230v
DIMENSIONI:	lunghezza: 2800mm larghezza: 1180mm altezza: 1800mm	DOTAZIONI DI SERIE:	avvisatore acustico di retromarcia, cruscotto digitale, luci anteriori e posteriori, clacson, indicatori di direzione, specchietti retrovisori laterali, parabrezza in plexiglass
DIM. VANBOX :	lunghezza: 800mm larghezza: 1100mm altezza: 1000mm capacità: 30 vassoi		
RAGGIO DI STERZATA:	3 mt	COLORI:	bianco

Tutti i dati riportati sono indicativi e non vincolanti, la ITALCAR INDUSTRIAL S.r.l. si riserva il diritto di apportarvi qualsiasi variazione senza alcun preavviso



ITALCAR INDUSTRIAL S.r.l. – Via Bruino, 36 – 10040 Rivalta di Torino
tel. 011.9040225 – fax 011.9032986
www.italcar.com - info@italcar.com



MODEL ATTIVA 2.4RS 48 V

2 PLACES WITH “ROOM SERVICE” INSULATED CARGO BOX

TECHNICAL FEATURES – ATTIVA 2.4RS

ENGINE:	AC 48v – Iskra	VOLTAGE:	48 volt
BATTERIES:	8 x 6volt mod. US battery 2200	SUSPENSION:	front: independent suspension rear: leaf springs with hydraulic shock absorbers
CONTROLLER:	SEVCON GEN4 for AC motors – 450Ah	CHASSIS:	galvanized steel frame and powder coated
		BODY:	main body: PP impregnated and painted 2 Places + insulated cargo box
TRANSMISSION:	rear axle, 19 spline, ratio 12,31:1	PERFORMANCES:	* max speed: 30 km/h * range: 80 km. * hill climbing ability: 15%
			datas are to be considered indicative and calculated on the average of different conditions of use
STEERING:	self compensating single reduction rack and pignon	TYRES:	205 / 50 – 10 - aluminium rims
BRAKES:	automotive types, double hydraulic circuit on four wheel with hand brake * Front: disc * Rear: drum	BATTERY CHARGER:	included with the vehicle - 48v, 220/230V
OVERALL DIMENSIONS:	length: 2700mm width: 1180mm height: 1800	BASIC CONFIGURATION:	* reverse buzzer; digital speedometer, front and rear lights, horn, direction indicators, rear-view mirrors, plexiglass
VAN DIMENSIONS:	length: 800mm width: 1100mm height: 1000mm capacity: 30 trays	COLOURS:	white
		TURNING RADIUS:	3 mt

All data reported are indicatives and not binding. ITALCAR INDUSTRIAL S.r.l. maintains the right to bring any changes without notice